

This document must not be copied, either completely or in part, without permission. Any infringement will have legal consequences ©




D


C

B

A



Quick action safety lock



1 : 1


D

C

B

A

Product No. 101161201	
Nominal flow Ø DN:	2.5 mm
Connection Stroke:	18.3 mm
Max WP Connected:	1500 bar
Max WP Disconnected:	1500 bar
Min BP Connected:	3000 bar
Min BP Disconnected:	3000 bar
Temperature range:	-30°C - +100°C
Connection:	G 1/8" Fem
Sealing material:	NBR
Hexagon:	24



20	1	Lip seal	NBR 80°±3° Shore (mtrl code N80/127)
19	1	Dust Cap	TPE, black
18	1	Sleeve	Steel, Zn-Ni 10 black
17	2	Ball	Stainless steel
16	1	Back part	Steel, Zn 8 silver
15	1	Locking sleeve	Hard.steel, Zn-Ni 10 black
14	9	Ball	Stainless steel
13	1	Spring	Stainless steel
12	1	O-ring	NBR
11	1	O-ring	NBR
10	1	Spring housing	Steel
9	1	O-ring sleeve	Steel
8	1	Expansion sleeve	Plastic
7	1	Washer	Steel
6	1	Spring	Steel
5	1	Seal	NBR
4	1	Valve	Steel, FeZn5
3	1	O-ring	NBR
2	1	Valve seat	Steel
1	1	Front part	Steel, Zn 8 silver
Item	Qty	Description	Material

Scale5:2

DrawnCABAO

CheckedFR

Appr.JE

ECO12061

Date2018-04-17

Assembly Drawing101161201

Drawing No.

IssueC

Sheet1/(1)