

This document must not be copied, either completely or in part, without permission. Any infringement will have legal consequences ©



A3

D

C

B




A

D

C


B

A



1 : 1

Product No. 102912205	
Nominal flow Ø DN:	5.5 mm
Connection Stroke:	21.3 mm
Max WP Connected:	12 bar
Min BP Connected:	48 bar
Temperature range:	-20°C - +100°C
Connection:	G 1/2" fem
Sealing material:	NBR
Hexagon:	20



11	1	Back part	Steel, Zn 8 Silver
10	1	Spring	Stainless steel
9	1	Spring	Stainless steel
8	1	Lip seal	NBR
7	1	Valve seat	Aluminium Lead Free
6	1	O-ring	NBR
5	1	O-ring	NBR
4	1	Valve	Aluminium Lead Free
3	1	Locking sleeve	Hard. steel, Zn 8 Silver
2	2	Hook	Hard. Steel, Zn-Ni 8 transp.
1	1	Front part	Hard. Steel, Zn-Ni 10 black
Item	Qty	Description	Material
State Production		Drawn CABLIJA	Checked ALAL
		Approved OSJO	Date 2025-01-14
 Coupling G 1/2" fem NBR - eSafe		ECO 002136	Former No.
		Scale 2 : 1	
		Drawing No. 102912205	
		Issue B	Sheet 1 /(1)