

This document must not be copied, either completely or in part, without permission. Any infringement will have legal consequences ©



D

C

B


A

D





C

B

A



1 : 1



Connection stroke

Product No. 103002005

Nominal flow Ø DN: 5,5 mm
Connection Stroke: 21,8 mm
Max WP Connected: 16 bar
Min BP Connected: 64 bar
Temperature range: -20°C - +100°C
Connection: Hose 1/2" 13mm
Sealing material: NBR
Hexagon: 20

11	1	Spring	Stainless steel	093003101
10	1	Locking sleeve	Hard. steel, Zn 8 Silver	093002540
9	2	Hook	Hard. Steel, Zn-Ni 8 transp.	093007040
8	1	Valve	Aluminium Lead Free	093003041
7	1	Valve seat	Aluminium Lead Free	093004022
6	1	Spring	Stainless steel	093003220
5	1	O-ring	NBR	094142800
4	1	O-ring	NBR	093002800
3	1	Lip seal	NBR	093003604
2	1	Front part	Hard. Steel, Zn-Ni 10 black	093002040
1	1	Back part	Steel, Zn 8 Silver	093054205

Item	Qty	Description	Material	Part Number
State		Drawn	Checked	Approved
Production		CABLIJA	ALAL	OSJO
		Date		2025-01-14
		ECO	Former No.	Scale
		002136		3 : 1
		Drawing No.	Issue	Sheet
		103002005	C	1 /(1)



Coupling 1/2" hose NBR - eSafe