

This document must not be copied, either completely or in part, without permission. Any infringement will have legal consequences ©



D

C

B


A

D



C

B

A



1:1



Connection stroke

12	1	Spring	Stainless steel
11	1	Locking sleeve	Hard. steel, Zn 8 Silver
10	2	Hook	Hard. Steel, Zn-Ni 8 transp.
9	1	Valve	Aluminium Lead Free
8	1	Valve seat	Aluminium Lead Free
7	1	Spring	Stainless steel
6	1	O-ring	NBR
5	1	O-ring	NBR
4	1	Lip seal	NBR
3	1	Front part	Hard. Steel, Zn-Ni 10 black
2	1	Swivel nut 8x12	Steel, Zn 8 Silver
1	1	Back part 8x12	Steel, Zn 8 Silver

Item	Qty	Description	Material
State		Drawn	Checked
Production		CABLIJA	ALAL
Approved		OSJO	Date
			2025-01-14
ECO		Former No.	Scale
002136			3 : 1
Drawing No.		Issue	Sheet
103002062		E	1 /(1)

Product No.	103002062
Nominal flow Ø DN:	5,5 mm
Connection Stroke:	21,8 mm
Max WP Connected:	16 bar w. CEJN braided PUR hose
Min BP Connected:	64 bar w. CEJN braided PUR hose
Temperature range:	-20°C - +100°C
Connection:	Stream-Line 8x12
Sealing material:	NBR
Hexagon:	See drawing



Coupling Stream-Line 8 x 12
mm NBR - eSafe