

This document must not be copied, either completely or in part, without permission. Any infringement will have legal consequences ©



D

C

B

A

D



C

B

A




1 : 1



12	1	Spring	Stainless steel
11	1	Locking sleeve	Hard. steel, Zn 8 Silver
10	2	Hook	Hard. Steel, Zn-Ni 8 transp.
9	1	Valve	Aluminium Lead Free
8	1	Valve seat	Aluminium Lead Free
7	1	Spring	Stainless steel
6	1	O-ring	NBR
5	1	O-ring	NBR
4	1	Lip seal	NBR
3	1	Front part	Hard. Steel, Zn-Ni 10 black
2	1	Swivel nut 11x16	Steel, Zn 8 Silver
1	1	Back part 11x16	Steel, Zn 8 Silver
Item	Qty	Description	Material

Product No.	103002066
Nominal flow Ø DN:	5,5 mm
Connection Stroke:	21,8 mm
Max WP Connected:	12 bar w. CEJN braided PUR hose
Min BP Connected:	48 bar w. CEJN braided PUR hose
Temperature range:	-20°C - +100°C
Connection:	Stream-Line 11x16
Sealing material:	NBR
Hexagon:	24 (2x)



Connection stroke

State	Drawn	Checked	Approved	Date
Production	CABLIJA	ALAL	OSJO	2025-01-14
ECO		Former No.		Scale
002136				3 : 1
Drawing No.			Issue	Sheet
103002066			D	1 /(1)



Coupling Stream-Line 11 x 16 mm NBR - eSafe