

This document must not be copied, either completely or in part, without permission. Any infringement will have legal consequences ©



D

C

B


A

D




C

B

A



1 : 1



Connection stroke

Product No.	103102004
Nominal flow Ø DN:	5,3 mm
Connection Stroke:	19,5 mm
Max WP Connected:	16 bar
Min BP Connected:	64 bar
Temperature range:	-20°C - +100°C
Connection:	Hose 3/8" 10mm
Sealing material:	NBR
Hexagon:	20

11	1	Valve	Aluminum Lead Free
10	1	Valve seat	Aluminium Lead Free
9	1	Spring	Stainless steel
8	1	Spring	Stainless steel
7	1	Lip seal	NBR
6	1	O-ring	NBR
5	1	O-ring	NBR
4	1	Locking sleeve	Hard. steel, Zn 8 Silver
3	2	Hook	Hard. Steel, Zn-Ni 8 transp.
2	1	Front part	Hard. Steel, Zn 8 Silver
1	1	Back part	Steel, Zn 8 Silver
Item	Qty	Description	Material

State	Production	Drawn	CABALAL	Checked	LIJA	Approved	OSJO	Date	2025-01-15
		Coupling 3/8" hose NBR - eSafe		ECO 002136		Former No.		Scale 3 : 1	
				Drawing No. 103102004		Issue C		Sheet 1 /(1)	