

This document must not be copied, either completely or in part, without permission. Any infringement will have legal consequences ©



D

C

B


A

D


C

B


A



1 : 1




* WP/BP is valid with CEJN non-braided hose



12	1	Valve	Aluminum Lead Free
11	1	Valve seat	Aluminium Lead Free
10	1	Spring	Stainless steel
9	1	Spring	Stainless steel
8	1	Lip seal	NBR
7	1	O-ring	NBR
6	1	O-ring	NBR
5	1	Locking sleeve	Hard. steel, Zn 8 Silver
4	2	Hook	Hard. Steel, Zn-Ni 8 transp.
3	1	Front part	Hard. Steel, Zn 8 Silver
2	1	Swivel nut	Steel, Zn 8 Silver
1	1	Back part	Steel, Zn 8 Silver

Item	Qty	Description	Material
State		Drawn	Checked
Production		CABALAL	LIJA
ECO		Approved	Date
002136		OSJO	2025-01-16
Drawing No.		Former No.	Scale
103102058			3 : 1
		Issue	Sheet
		C	1 /(1)



Connection stroke

Product No.	103102058
Nominal flow Ø DN:	4,5 mm
Connection Stroke:	19,5 mm
Max WP Connected:	10 bar *
Min BP Connected:	25 bar *
Temperature range:	-20°C - +100°C
Connection:	Stream-Line 5x8
Sealing material:	NBR
Hexagon:	See drawing



Coupling Stream-Line 5x8
mm NBR - eSafe