

This document must not be copied, either completely or in part, without permission. Any infringement will have legal consequences ©



D

C

B


A

D


C

B



A



1 : 1



Product No. 103102402	
Nominal flow Ø DN:	5,3 mm
Connection Stroke:	19,5 mm
Max WP Connected:	16 bar
Min BP Connected:	140 bar
Temperature range:	-20°C - +100°C
Connection:	NPT 1/4" Fem
Sealing material:	NBR
Hexagon:	20



11	1	Valve	Aluminum Lead Free
10	1	Valve seat	Aluminium Lead Free
9	1	Spring	Stainless steel
8	1	Spring	Stainless steel
7	1	Lip seal	NBR
6	1	O-ring	NBR
5	1	O-ring	NBR
4	1	Locking sleeve	Hard. steel, Zn 8 Silver
3	2	Hook	Hard. Steel, Zn-Ni 8 transp.
2	1	Front part	Hard. Steel, Zn 8 Silver
1	1	Back part	Steel, Zn 8 silver

Item	Qty	Description	Material	
State		Drawn	Checked	Approved
Production		CABALAL	LIJA	OSJO
ECO		Former No.		Date
002136				2025-01-20
Drawing No.		Issue		Scale
103102402		B		1 : 1
		Sheet		
		1 /(1)		

