

This document must not be copied, either completely or in part, without permission. Any infringement will have legal consequences ©



A3

D

C

B


A

D



C

B

A




1 : 1



11	1	Valve seat	Aluminium Lead Free
10	1	Valve	Aluminium Lead Free
9	1	Spring	Stainless steel
8	1	Spring	Stainless steel
7	1	Lip seal	NBR
6	1	O-ring	NBR
5	1	O-ring	NBR
4	1	Locking sleeve	Hard. steel, Zn 8 Silver
3	2	Hook	Hard. Steel, Zn-Ni 8 transp.
2	1	Front part	Hard. Steel, Zn 8 silver
1	1	Back part	Steel, Zn 8 Silver
Item	Qty	Description	Material

Product No.	103202454
Nominal flow Ø DN:	7,6 mm
Connection Stroke:	19,2 mm
Max WP Connected:	16 bar
Min BP Connected:	140 bar
Temperature range:	-20°C - +100°C
Connection:	NPT 3/8"Male
Sealing material:	NBR
Hexagon:	20



Connection stroke

State	Drawn	Checked	Approved	Date
Production	CABALAL	LIJA	OSJO	2025-02-06
ECO		Former No.		Scale
002136				1 : 1
Drawing No.			Issue	Sheet
103202454			B	1 /(1)



Coupling 3/8" NPT male NBR - eSafe