

This document must not be copied, either completely or in part, without permission. Any infringement will have legal consequences ©



D

C

B


A

D



C

B


A




1 : 1



12	1	Valve seat	Aluminum Lead Free
11	1	Locking sleeve	Hard. Steel, Zn 8 silver
10	1	Spring	Stainless Steel
9	1	Spring	Stainless Steel
8	1	Lip seal	NBR
6	1	O-ring	NBR
5	1	O-ring	NBR
4	1	Valve	Aluminum Lead Free
3	3	Hook	Hard. Steel, Zn-Ni 8 transp.
2	1	Front part	Hard. Steel Zn 8 Silver
1	1	Back part	Steel, Zn 8 Silver



Item	Qty	Description	Material
State		Drawn	Checked
Production		CABLIJA	ALAL
Approved		OSJO	Date
			2025-05-09
ECO		Former No.	Scale
002136			2 : 1
Drawing No.		Issue	Sheet
104302154		C	1 /(1)



Connection stroke

Product No. 104302154

Nominal flow $\varnothing$ DN: 8.2 mm
Connection Stroke: 23.6 mm
Max WP Connected: 16 bar
Min BP Connected: 140 bar
Temperature range: -20°C - +100°C
Connection: R 3/8" Male
Sealing material: NBR

6

5

4

3

2

1