

This document must not be copied, either completely or in part, without permission. Any infringement will have legal consequences ©



D

C

B


A

D


C

B


A




1 : 1



Product No. 105502155	
Nominal flow Ø DN:	11 mm
Connection Stroke:	27,9 mm
Max WP Connected:	16 bar
Min BP Connected:	140 bar
Temperature range:	-20°C - +100°C
Connection:	R 1/2"
Sealing material:	NBR
Hexagon:	26



Connection stroke



11	1	Valve	Aluminum Lead Free
10	1	Valve seat	Aluminum Lead free
9	1	Lip seal	NBR
8	1	Locking sleeve	Hard. Steel Zn 8 silver
7	3	Hook	Hard. Steel Zn-Ni 8 transp.
6	1	Spring	Stainless Steel
5	1	Spring	Stainless steel
4	1	O-ring	NBR
3	1	Quad-Ring	NBR
2	1	Front part	Hard. Steel Zn 8 silver
1	1	Back part	Steel, Zn 8 Silver
Item	Qty	Description	Material

State Production		Drawn CABLIJA	Checked ALAL	Approved OSJO	Date 2025-03-31
 Coupling R 1/2" male NBR		ECO 002136		Former No.	
		Drawing No. 105502155		Issue B	Scale 2 : 1 Sheet 1 /(1)