


This document must not be copied, either completely or in part, without permission. Any infringement will have legal consequences ©



Product No. 109071405	
Nominal flow Ø DN:	32 mm
Connection Stroke:	mm
Max WP Connected:	380 bar
Max WP Disconnected:	380 bar
Min BP Connected:	1520 bar
Min BP Disconnected:	1000 bar
Temperature range:	-30°C - +120°C
Connection:	1 1/2" NPT
Sealing material:	HNBR
Hexagon:	

14	1	O-ring	HNBR
13	1	O-ring	HNBR
12	1	Back part	Steel, Zn-Ni transp
11	1	Back-up	PTFE
10	1	O-ring	NBR
9	1	Back-up ring	PTFE+Bronze
8	1	Back-up ring	PTFE+Bronze
7	1	O-ring	HNBR
6	1	Retaining ring	Steel
5	1	Washer	Steel
4	1	Semi A. valve package	
3	1	Spring	Steel
2	1	Valve	Steel, Zn-Ni transp.
1	1	Coupling body	Hardened steel, Zn-Ni
Item	Qty	Description	Material

State Production		Drawn CABANUN	Checked PESV	Approved JOER	Date 2024-06-05		
	Coupling TLX 1 1/2" - 1 1/2" NPT fem HNBR			ECO 001683		Former No.	Scale 1 : 1
				Drawing No. 109071405		Issue B	Sheet 1 /(1)