

This document must not be copied, either completely or in part, without permission. Any infringement will have legal consequences ©



A3

D


C

B


D

C

B



1 : 2



Product No. 109076207	
Nominal flow Ø DN:	32 mm
Connection Stroke:	mm
Max WP Connected:	380 bar
Max WP Disconnected:	380 bar
Min BP Connected:	1520 bar
Min BP Disconnected:	1000 bar
Temperature range:	-30°C - +120°C
Connection:	G 2"
Sealing material:	HNBR
Hexagon:	

9	1	O-ring	HNBR
8	1	O-ring	HNBR
7	1	Semi A. - Valve HNBR	
6	1	Semi A. Lock. pin + wire	
5	1	Semi A. Nipple Body	
4	1	Wire coil	Stainless steel
3	1	Spring	Stainless steel
2	1	Back part	Steel, Zn-Ni transp.
1	1	Locking sleeve	Steel, Zn-Ni transp
Item	Qty	Description	Material
State Production		Drawn CABANUN	Checked PESV
		Approved JOER	Date 2024-06-05
		ECO 001683	Former No.
		Scale 1 : 1	
		Drawing No. 109076207	Issue B
			Sheet 1 /(1)



Nipple TLX 1 1/2" - G 2" fem
HNBR