

This document must not be copied, either completely or in part, without permission. Any infringement will have legal consequences ©





D

C

B

A



D

C

B

A

Product No. 112100150	
Nominal flow Ø DN:	mm
Connection Stroke:	mm
Max WP Connected:	16 bar
Min BP Connected:	64 bar
Temperature range:	-20°C - +60°C@16 bar WP,+80°C@10 bar WP
Connection:	1/4" NPT female
Sealing material:	NBR
Hexagon:	

19	1	Tube cap	Plastic
18	1	MF Tube - 90mm	Brass, Plated
17	1	Nozzle adapter	Plastic
16	1	Adapter	Steel, Zn 8 P1/N
15	1	Guide bushing	Plastic
14	1	O-ring	NBR
13	1	O-ring	NBR
12	1	Lip seal	NBR
11	1	Valve	Plastic
10	1	O-ring	NBR
9	1	Label	Plastic
8	1	Spring	Stainless steel
7	1	O-ring	NBR
6	1	Screw	Steel
5	1	Wheel	Plastic
4	1	Spacer	Plastic
3	1	Valve ball	Plastic
2	1	Handle	Plastic
1	1	Body	Plastic
Item	Qty	Description	Material

Scale1 : 2

Drawn CABANLA

Checked CABLHE

Appr. CABJOOL

ECO

Date2017-11-08

IssueAB

Sheet1 /(1)

Assembly Drawing

502100150