


C(D)85-S/T, ISO Cylinder, Single Acting, Single Rod CD85N16-25S-A

- Single acting, single rod, spring return/spring extend
- Conforms to ISO standard 6432
- Bore sizes (mm): 8, 10, 12, 16, 20, 25
- Standard strokes up to 150mm
- Auto switch capable



Single-acting cylinder, single piston rod, return stroke by spring

Magnet	D (Built-in)
Mounting	N (Basic Integrated Clevis)
Bore Size	Ø16 mm
Stroke	25
Action	S (Spring Return)
Switch Mounting	A (Rail)
Auto Switch	No Switch
Lead Wire or Prewired Connector	0.5m (Or None in the Case of No Switch)
Number	2 pcs. (Or None in the Case of No Switch)
Rod End Options	None
Made of Stainless Steel	None
-	Compressed air
Maximum temperature of pressure medium with magnet	80°C
Minimum temperature of pressure medium with magnet	-20°C
Maximum operating pressure	1 MPa
Minimum operating pressure	0.13 Mpa
Proof pressure	1.5 MPa
Maximum ambient temperature with magnet	80°C
Minimum ambient temperature with magnet	-20°C

Pneumatic input connection	M5
Pneumatic output connection	M5
Mode of operation of drive single	Single acting, spring return
Maximum piston speed	1500 mm/s
Type of cushioning	Rubber bumper
Piston rod end	External thread
Male thread of rod end	M6
Weight	0.119 Kg





Tabelle														Datei		
	AM	BE	C	DE	EE	EW	P	W	HR	K	KA	XX	XX	XX	XX	XX
1987	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
1	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
2	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
3	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
4	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
5	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
6	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
7	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
8	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
9	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
10	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
11	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
12	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
13	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
14	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
15	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
16	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
17	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
18	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
19	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
20	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
21	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
22	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
23	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
24	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
25	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
26	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
27	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
28	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
29	1	2	3	4	5	6</										

Single acting: Single rod Spring return/C□85□8 to 16-□S (Disassembly is not possible)



Component Parts

No.	Description	Material	Quantity	Remarks
①	Rod cover	Aluminum alloy	1	White anodized
②A	Head cover N	Aluminum alloy	1	White anodized
②B	Head cover E	Aluminum alloy	1	White anodized
②C	Head cover F	Aluminum alloy	1	White anodized
②D	Head cover Y	Aluminum alloy	1	White anodized
③	Cylinder tube	Stainless steel	1	
④	Piston rod	Stainless steel	1	
⑤	Piston	Brass	1	
⑥	Piston A	Brass	1	(Switch style only)
⑦	Piston B	Brass	1	(Switch style only)
⑧	Bushing	Sintered bronze	1	

No.	Description	Material	Quantity	Remarks
⑨	Magnet		1	(Switch style only)
⑩	Bumper	Urethane	2	
⑪	Return spring A	Piano wire	1	
⑫	Return spring B	Piano wire	1	
⑬	Spring guide	Brass	1	
⑭	Spacer	Brass	1	
⑮	Piston gasket	NBR	1	
⑯	Tube gasket	NBR	1	
⑰	Piston seal	NBR	1	
⑱	Rod end nut	Carbon steel	1	Nickel plated
⑲	Mounting nut	Carbon steel	1	Nickel plated

-

-

C85_C75-A_EU.pdf