


C(D)85, Vérin aux normes ISO, double effet, simple tige C85N10-20

Fiche technique

- ISO 6432 Vérin à corps rond.
- Alésages (mm) : 8, 10, 12, 16, 20, 25.
- Courses standard jusqu'à 300 mm.
- Variantes de Vérin : Anti-rotation, montage direct, ATEX.







Vérin double effet, simple tige

Standard Specifications

Aimant	Sans
Montage	N (Tenon arrière intégré standard)
Alésage	Ø10 mm
Course	20
Amortissement	Amortissement élastique
Soufflet de tige	Sans
Type de montage du détecteur	Sans
Options d'extrémités de tige	Sans
Résistance aux températures	Sans
Faible vitesse	Sans
Acier inox	Sans
Course Longue	Sans
Pression du fluide	Air
Température maximum du fluide	80 °C
Température du fluide min.	-20 °C
Maximum operating pressure	1 MPa
F007-MIN_OP_PRESSURE	0.08 MPa
Proof pressure	1.5 MPa
Température ambiante max.	80 °C
Température ambiante min.	-20 °C

Conforme à la directive européenne RoHS	Conforme
Nombre de connecteurs pneumatiques	2 pcs.
Pneumatic input connection	M5
Raccord de sortie pneumatique	M5
Action	Double effet
Theoretical cylinder force, advance stroke (at 0.5 MPa)	39.3 N
Theoretical cylinder force, return stroke (at 0.5 MPa)	33.0 N
Maximum piston speed	1,500 mm/s
Type d'amortissement	Rubber bumper
Piston rod end	Filetage extérieur
Forme géométrique de la tige de piston	Tige simple
Male thread of rod end	M4
Minimum piston speed	50 mm/s
Weight	0.055 Kg


Dimensions



Constructions

Double acting: Single rod

C□85□8 to16 Rubber bumper (Disassembly is not possible)



Component Parts

No.	Description	Material	Quantity	Remarks
①	Rod cover	Aluminum alloy	1	White anodized
②A	Head cover N	Aluminum alloy	1	White anodized
②B	Head cover E	Aluminum alloy	1	White anodized
②C	Head cover F	Aluminum alloy	1	White anodized
②D	Head cover Y	Aluminum alloy	1	White anodized
③	Cylinder tube	Stainless steel	1	
④	Piston rod	Stainless steel	1	
⑤A	Piston A	Brass	1	
⑤B	Piston B	Brass	2	(Switch style piston)

No.	Description	Material	Quantity	Remarks
⑥	Bushing	Sintered bronze	1	
⑦	Magnet		1	(Switch style only)
⑧	Bumper	Urethane	2	
⑨	Piston gasket	NBR	1	(2 for switch style)
⑩	Tube gasket	NBR	2	
⑪	Rod seal	NBR	1	
⑫	Piston seal	NBR	2	
⑬	Rod end nut	Carbon steel	1	Nickel plated
⑭	Mounting nut	Carbon steel	1	Nickel plated

Information supplémentaire

Catalogue

[C85_C75-A_FR.pdf](#)