



C(D)85K, ISO Cylinder, Double Acting, Single Rod, Non-Rotating C85KN25-200

Datasheet

General series information

- ISO cylinder, double acting, single rod
- Bore sizes (mm): 8, 10, 12, 16, 20, 25
- Type: non-rotating
- Cushion: rubber bumper only
- Strokes (mm): up to 300 (depending on bore)
- Auto switches available (order separate)




Double-acting cylinder, non-rotating single piston rod

Standard specifications

Magnet	None
Mounting	N (Basic Integrated Clevis)
Bore Size	Ø25 mm
Stroke	200
Switch Mounting	No Switch
Auto Switch	No Switch
Lead Wire or Prewired Connector	0.5m (Or None in the Case of No Switch)
Number	2 pcs. (Or None in the Case of No Switch)
Rod End Options	None
Made of Stainless Steel	None
Long Stroke	None
Pressure medium	Compressed air
Maximum temperature of pressure medium	80 °C
Minimum temperature of pressure medium	-20 °C
Maximum operating pressure	1 MPa
Minimum operating pressure	0.05 MPa
Proof pressure	1.5 MPa

Maximum ambient temperature	80 °C
Minimum ambient temperature	-20 °C
Number of pneumatic connections	2 pcs.
Pneumatic input connection	G 1/8
Pneumatic output connection	G 1/8
Mode of operation of drive	Double acting
Theoretical cylinder force, advance stroke (at 0.5 MPa)	245.5 N
Theoretical cylinder force, return stroke (at 0.5 MPa)	206.2 N
Maximum piston speed	1500 mm/s
Type of cushioning	Rubber bumper
Piston rod end	External thread
Geometric form of the piston rod	Single rod
Male thread of rod end	M10 x 1.25
Tolerance of torsion	±0° 42'

Dimensions



寸法表

シリーズ	AM	BE	C	CD	D	EE	EW	F	G	Gu	H	HR	K	KA	KK	KV	Ni	Nu	NA	NC	RR	S	SW	U	WA	Wh	XC	Z	ZZ
8	12	M7×1.25	4.4	16.3	WS×0.8	8.12	F	5	20	10	—	4.2	M4×0.7	10	4	11.5	9.5	15	12	10	45	7	6	—	10	62	75	89	
10	12	M12×1.25	4.4	16.3	WS×0.8	8.12	F	5	20	10	—	4.2	M4×0.7	10	4	11.5	9.5	15	12	10	45	7	6	10.5	10	64	75	89	
12	16	M16×1.5	6.6	19.3	WS×0.8	12.17	F	5	20	10	—	4.2	M4×0.7	10	4	11.5	9.5	15	12	10	45	7	6	10.5	10	64	75	89	
16	16	M16×1.5	6.6	19.3	WS×0.8	12.17	F	5	20	10	—	4.2	M4×0.7	10	4	11.5	9.5	15	12	10	45	7	6	10.5	10	64	75	89	
20	20	M22×1.5	8.8	28	G 1/8	16.20	B	8	44	17	—	6.3	M6×1.25	32	11	17	15	17	24	22	11	62	13	12	23	26	95	115	126
25	25	M27×1.5	10.8	33	G 1/8	16.20	B	8	44	20	—	6.3	M6×1.25	32	11	17	15	17	24	22	11	62	13	12	23	26	95	115	126

()内はエアクッションの寸法。

ジャバラ付


シリーズ	AM	C	e	f	K	KK	h
8	20	8	36	20	8	M6×1.25	71
10	22	10	36	20	8	M10×1.25	74

ジャバラ付

シリーズ	AM	C	e	f	K	KK	h
8	20	8	36	20	8	M6×1.25	71
10	22	10	36	20	8	M10×1.25	74

Constructions

C□85□20, 25 Rubber bumper



Component Parts

No.	Description	Material	Quantity	Remarks
①	Rod cover	Aluminum alloy	1	White anodized
②A	Head cover N	Aluminum alloy	1	White anodized
②B	Head cover E	Aluminum alloy	1	White anodized
②C	Head cover F	Aluminum alloy	1	White anodized
②D	Head cover Y	Aluminum alloy	1	White anodized
③	Cylinder tube	Stainless steel	1	
④	Piston rod	Carbon steel	1	Hard chrome plated
⑤	Piston	Aluminum alloy	1	Chromated
⑥	Plain washer	Carbon steel	1	Nickel plated
⑦	Bushing	Sintered bronze	1	
⑧	Bushing	Sintered bronze	2	

* Stainless steel (Non-rotating rod)

No.	Description	Material	Quantity	Remarks
⑨	Retaining ring	Carbon steel	1	Nickel plated
⑩	Retaining ring	Carbon steel	2	
⑪	Magnet		1	(Switch style only)
⑫	Wear ring	Phenolic resin	1	
⑬	Bumper A	Urethane	1	
⑭	Bumper B	Urethane	1	
⑮	Piston gasket	NBR	1	
⑯	Rod seal	NBR	1	
⑰	Piston seal	NBR	1	
⑱	Rod end nut	Carbon steel	1	Nickel plated
⑲	Mounting nut	Carbon steel	1	Nickel plated

Additional information

Catalogue

[C85_C75-A_EU.pdf](#)