




## C(D)Q2, Compact Cylinder, Double Acting, Single Rod, Large Bore w/Auto Switch Mounting Groove

### CQ2B160TF-125DCZ

Datasheet

### General series information

- Compact, double acting, single rod, large bore
- Bore sizes (mm): 125, 140, 160, 180, 200
- Standard stroke range (mm): 10 to 300
- Port threads: Rc, NPT, G
- Can mount small auto switches on 4 surfaces.





Double-acting, single-rod cylinder

### Standard specifications



|                                        |                                        |
|----------------------------------------|----------------------------------------|
| Magnet                                 | None                                   |
| Bore Size                              | Ø160 mm                                |
| Port Thread Type                       | TF (G)                                 |
| Stroke                                 | 125                                    |
| Body Option                            | Standard (Rod End Female Thread)       |
| Auto Switch                            | No Switch                              |
| Lead Wire or Prewired Connector        | 0.5 m or None in the Case of No Switch |
| Number                                 | 2 pcs.                                 |
| Rod End Options                        | None                                   |
| Fluororubber Seal                      | None                                   |
| -                                      | Compressed air                         |
| Maximum temperature of pressure medium | 70 °C                                  |
| Minimum temperature of pressure medium | -10 °C                                 |
| Maximum operating pressure             | 1.0 MPa                                |
| Minimum operating pressure             | 0.05 MPa                               |
| Proof pressure                         | 1.5 MPa                                |
| Maximum ambient temperature            | 70 °C                                  |
| Minimum ambient temperature            | -10 °C                                 |

|                                                         |             |
|---------------------------------------------------------|-------------|
| Pneumatic input connection                              | G 3/8       |
| Theoretical cylinder force, advance stroke (at 0.5 MPa) | 9,425 N     |
| Theoretical cylinder force, return stroke (at 0.5 MPa)  | 10,053 N    |
| Maximum piston speed                                    | 500 mm/s    |
| Piston rod end                                          | Male thread |
| Male thread of rod end                                  | M36 x 1.5   |
| Female thread of rod end                                | M24 x 3     |
| Minimum piston speed                                    | 50 mm/s     |
| Weight                                                  | 13.090 Kg   |

# Dimensions



## Constructions



### Component Parts

| No. | Description    | Material          | Note               |
|-----|----------------|-------------------|--------------------|
| 1   | Cylinder tube  | Aluminum alloy    | Hard anodised      |
| 2   | Head cover     | Carbon steel      | Nickel plated      |
| 3   | Piston         | Aluminum alloy    | Chromated          |
| 4   | Piston rod     | Carbon steel      | Hard chrome plated |
| 5   | Rod cover      | Carbon steel      | Nickel plated      |
| 6   | Retaining ring | Carbon tool steel | Phosphate coated   |
| 7   | Bumper         | Urethane          |                    |
| 8   | Bushing        | Bearing alloy     |                    |
| 9   | Wear ring      | Resin             |                    |
| 10  | Magnet         | —                 | For CDQ2B□ only    |
| 11  | Rod end nut    | Carbon steel      | Nickel plated      |
| 12  | Piston seal    | NBR               |                    |
| 13  | Rod seal       | NBR               |                    |
| 14  | Tube gasket    | NBR               |                    |

### Replacement Parts/Seal Kit

| Bore size (mm) | Kit no.    | Contents                                      |
|----------------|------------|-----------------------------------------------|
| 125            | CQ2B125-PS | Kits include items 12, 13, 14 from the table. |
| 140            | CQ2B140-PS |                                               |
| 160            | CQ2B160-PS |                                               |
| 180            | CQ2B180-PS |                                               |
| 200            | CQ2B200-PS |                                               |

\* Seal kit includes 12, 13, 14. Order the seal kit, based on each bore size.  
 \* Since the seal kit does not include a grease pack, order it separately.

**Grease pack part no.: GR-S-010 (10 g)**

## Additional information

Catalogue

[CQ2-Z-B\\_EU.pdf](#)