




## C(D)Q2, Compact Cylinder, Double Acting Single Rod, Long Stroke w/Auto Switch Mounting Groove CQ2F50-150DCZ

Datasheet

### General series information

- Compact Cylinder: Long Stroke Double Acting, Single Rod
- Bore sizes (mm): 32, 40, 50, 63, 80, 100
- Standard stroke range (mm): 125 to 300
- Port threads: Rc, NPT or G
- Can mount small auto switches on 4 surfaces.



Double-acting, single-rod cylinder


### Standard specifications

|                                        |                                          |
|----------------------------------------|------------------------------------------|
| Magnet                                 | None                                     |
| Mounting                               | F (Front Flange)                         |
| Type                                   | Standard                                 |
| Bore Size                              | Ø50 mm                                   |
| Port Thread                            | Rc                                       |
| Stroke                                 | 150                                      |
| Cushion                                | C (Rubber Bumper)                        |
| Body Option                            | Standard (Rod End Female Thread)         |
| Auto Switch                            | No Switch                                |
| Lead Wire or Pre-wired Connector       | 0.5 m (Or None in the Case of No Switch) |
| Number                                 | 2 pcs.                                   |
| Rod End Options                        | None                                     |
| Made of Stainless Steel                | None                                     |
| Fluororubber Seal                      | None                                     |
| Pressure medium                        | Compressed air                           |
| Maximum temperature of pressure medium | 70 °C                                    |
| Minimum temperature of pressure medium | -10 °C                                   |
| Maximum operating pressure             | 1.0 MPa                                  |

|                                  |               |
|----------------------------------|---------------|
| Minimum operating pressure       | 0.05 MPa      |
| Proof pressure                   | 1.5 MPa       |
| Maximum ambient temperature      | 70 °C         |
| Minimum ambient temperature      | -10 °C        |
| Number of pneumatic connections  | 2 pcs.        |
| Pneumatic input connection       | Rc 1/4        |
| Mode of operation of drive       | Double acting |
| Maximum piston speed             | 500 mm/s      |
| Type of cushioning               | Elastically   |
| Piston rod end                   | Female-Thread |
| Geometric form of the piston rod | Single rod    |
| Male thread of rod end           | M18 x 1.5     |
| Female thread of rod end         | M10 x 1.5     |
| Minimum piston speed             | 50 mm/s       |
| Weight                           | 1.605 Kg      |

## Dimensions

### ロッド側フランジ形／C□Q2F




### ロッド側フランジ形


| チューブ内径<br>(mm) | A    | B    | FD  | FT | FV | FX | FZ | L  | L <sub>1</sub> | M  |
|----------------|------|------|-----|----|----|----|----|----|----------------|----|
| 32             | 62.5 | 45.5 | 5.5 | 8  | 48 | 56 | 65 | 17 | 38.5           | 34 |
| 40             | 72   | 55   | 5.5 | 8  | 54 | 62 | 72 | 17 | 38.5           | 40 |
| 50             | 73.5 | 55.5 | 6.6 | 9  | 67 | 76 | 89 | 18 | 43.5           | 50 |

フランジ金具材質: 炭素鋼  
表面処理: ニッケルめっき

### ロッド先端おねじ



## Constructions



### Component Parts

| No. | Description       | Material          | Note               |
|-----|-------------------|-------------------|--------------------|
| 1   | Cylinder tube     | Aluminum alloy    | Hard anodised      |
| 2   | Piston            | Aluminum alloy    | Chromated          |
| 3   | Piston rod        | Carbon steel      | Hard chrome plated |
| 4   | Collar            | Aluminum alloy    | Anodised           |
| 5   | Bottom plate      | Aluminum alloy    | Anodised           |
| 6   | Retaining ring    | Carbon tool steel | Phosphate coated   |
| 7   | Bumper A          | Urethane          |                    |
| 8   | Bumper B          | Urethane          |                    |
| 9   | Bushing           | Bearing alloy     |                    |
| 10  | Wear ring         | Resin             |                    |
| 11  | Rod end nut       | Carbon steel      | Nickel plated      |
| 12  | Magnet            | —                 | For CDQ2A□ only    |
| 13  | One-touch fitting | —                 | ø32 to ø63         |
| 14* | Rod seal          | NBR               |                    |
| 15* | Piston seal       | NBR               |                    |
| 16* | Tube gasket       | NBR               |                    |

### Replacement Parts/Seal Kit

| Bore size (mm) | Kit no.      | Contents                                      |
|----------------|--------------|-----------------------------------------------|
| 32             | CQ2A32-L-PS  | Kits include items 14, 15, 16 from the table. |
| 40             | CQ2A40-L-PS  |                                               |
| 50             | CQ2A50-L-PS  |                                               |
| 63             | CQ2A63-L-PS  |                                               |
| 80             | CQ2A80-L-PS  |                                               |
| 100            | CQ2A100-L-PS |                                               |

\* Seal kit includes 14, 15, 16. Order the seal kit, based on each bore size.

\* Since the seal kit does not include a grease pack, order it separately.

**Grease pack part no.: GR-S-010 (10 g)**

## Additional information

|                   |                                       |
|-------------------|---------------------------------------|
| Catalogue         | <a href="#">CQ2-Z-D_EU.pdf</a>        |
| Operation manuals | <a href="#">OM_CQ2x_OM0002MEN.pdf</a> |