




## C(D)Q2, Compact Cylinder, Double Acting Single Rod, Long Stroke w/Auto Switch Mounting Groove CQ2L50-150DCZ

- Compact Cylinder: Long Stroke Double Acting, Single Rod
- Bore sizes (mm): 32, 40, 50, 63, 80, 100
- Standard stroke range (mm): 125 to 300
- Port threads: Rc, NPT or G
- Can mount small auto switches on 4 surfaces.




Double-acting, single-rod cylinder

|                                        |                                        |
|----------------------------------------|----------------------------------------|
| Magnet                                 | None                                   |
| Mounting                               | L (Foot)                               |
| Type                                   | Standard                               |
| Bore Size                              | Ø50 mm                                 |
| Port Thread Type                       | Rc                                     |
| Stroke                                 | 150                                    |
| Cushion                                | C (Rubber Bumper)                      |
| Body Option                            | Standard (Rod End Female Thread)       |
| Auto Switch                            | No Switch                              |
| Lead Wire or Prewired Connector        | 0.5 m or None in the Case of No Switch |
| Number                                 | 2 pcs.                                 |
| Rod End Options                        | None                                   |
| Made of Stainless Steel                | None                                   |
| Fluororubber Seal                      | None                                   |
| -                                      | Compressed air                         |
| Maximum temperature of pressure medium | 70 °C                                  |
| Minimum temperature of pressure medium | -10 °C                                 |
| Maximum operating pressure             | 1.0 MPa                                |

|                             |               |
|-----------------------------|---------------|
| Minimum operating pressure  | 0.05 MPa      |
| Proof pressure              | 1.5 MPa       |
| Maximum ambient temperature | 70 °C         |
| Minimum ambient temperature | -10 °C        |
| Pneumatic input connection  | Rc 1/4        |
| Maximum piston speed        | 500 mm/s      |
| Type of cushioning          | Elastically   |
| Piston rod end              | Female-Thread |
| Male thread of rod end      | M18 x 1.5     |
| Female thread of rod end    | M10 x 1.5     |
| Minimum piston speed        | 50 mm/s       |


フート形／C□Q2L




| フート形<br>(mm) | A    | B    | L  | L <sub>1</sub> | LD  | LG | LH | LS   | LT  | LX | LY | LZ | X    | Y   |
|--------------|------|------|----|----------------|-----|----|----|------|-----|----|----|----|------|-----|
| 32           | 69.3 | 45.5 | 17 | 38.5           | 6.6 | 4  | 30 | 29.5 | 3.2 | 57 | 57 | 71 | 11.2 | 5.8 |
| 40           | 78.2 | 55   | 17 | 38.5           | 6.6 | 4  | 32 | 39   | 3.2 | 64 | 64 | 78 | 11.2 | 7   |
| 50           | 81.7 | 55.5 | 18 | 43.5           | 9   | 5  | 39 | 32.5 | 3.2 | 79 | 78 | 95 | 7.4  | 8   |

※L<sub>1</sub>: 変形材料、標準値


フットボール材料: 皮革調  
表面処理: ニックルめっき



Rod end male thread



Built-in one-touch fittings



## Component Parts

| No. | Description       | Material          | Note               |
|-----|-------------------|-------------------|--------------------|
| 1   | Cylinder tube     | Aluminum alloy    | Hard anodised      |
| 2   | Piston            | Aluminum alloy    | Chromated          |
| 3   | Piston rod        | Carbon steel      | Hard chrome plated |
| 4   | Collar            | Aluminum alloy    | Anodised           |
| 5   | Bottom plate      | Aluminum alloy    | Anodised           |
| 6   | Retaining ring    | Carbon tool steel | Phosphate coated   |
| 7   | Bumper A          | Urethane          |                    |
| 8   | Bumper B          | Urethane          |                    |
| 9   | Bushing           | Bearing alloy     |                    |
| 10  | Wear ring         | Resin             |                    |
| 11  | Rod end nut       | Carbon steel      | Nickel plated      |
| 12  | Magnet            | —                 | For CDQ2A□ only    |
| 13  | One-touch fitting | —                 | ø32 to ø63         |
| 14* | Rod seal          | NBR               |                    |
| 15* | Piston seal       | NBR               |                    |
| 16* | Tube gasket       | NBR               |                    |

## Replacement Parts/Seal Kit

| Bore size (mm) | Kit no.      | Contents                                      |
|----------------|--------------|-----------------------------------------------|
| 32             | CQ2A32-L-PS  | Kits include items 14, 15, 16 from the table. |
| 40             | CQ2A40-L-PS  |                                               |
| 50             | CQ2A50-L-PS  |                                               |
| 63             | CQ2A63-L-PS  |                                               |
| 80             | CQ2A80-L-PS  |                                               |
| 100            | CQ2A100-L-PS |                                               |

\* Seal kit includes 14, 15, 16. Order the seal kit, based on each bore size.

\* Since the seal kit does not include a grease pack, order it separately.

**Grease pack part no.: GR-S-010 (10 g)**

-

-

CQ2-Z-B\_EU.pdf