




C(D)Q2, Compact Cylinder, Double Acting, Single Rod w/Auto Switch Mounting Groove CDQ2A40-30DFZ

- Double acting, single rod, compact cylinder
- Bore sizes (mm): 12, 16, 20, 25, 32, 40, 50, 63, 80, 100
- Standard stroke range (mm): 5 to 100
- Port threads: M (12 to 25 bore); Rc, NPT or G (32 to 100 bore)
- Can mount small auto switches on 4 surfaces.

Magnet	D (Built-in)
Mounting	A (Both Ends Tapped)
Type	Standard
Bore Size	Ø40 mm
Port Thread Type	Rc
Lube-retainer	Without Stable Lubrication Function
Stroke	30
Body Option	F [Rear Boss Mount]
Auto Switch Groove	None, also for 12-25 Bore w/o Magnet
Mounting Bolt	None
Rod End Bracket	None
Auto Switch	No Switch
Lead Wire or Prewired Connector	Z (5 m)
Number	2 pcs.
Rod End Options	None
Temperature Resistance	None
Low Speed	None
Made of Stainless Steel	None

Fluororubber Seal	None
-	Compressed air
Weight	0.381 Kg

032-e50

オートミックス計



標準型 7.5kWタイプ / COB-COB200



標準型 7.5kWタイプ / COB-COB200



標準型 7.5kWタイプ / COB-COB200



標準型 7.5kWタイプ / COB-COB200



標準型 7.5kWタイプ / COB-COB200



標準型 7.5kWタイプ / COB-COB200



オプション型 7.5kWタイプ / COB-COB200



オプション型 7.5kWタイプ / COB-COB200



オプション型 7.5kWタイプ / COB-COB200



標準型 7.5kWタイプ / COB-COB200



標準型 7.5kWタイプ / COB-COB200



標準型 7.5kWタイプ / COB-COB200



-

-

CQ2-Z-B_EU.pdf