





C(D)Q2, Compact Cylinder, Double Acting, Single Rod w/Auto Switch Mounting Groove CDQ2D16-25DZ

- Double acting, single rod, compact cylinder
- Bore sizes (mm): 12, 16, 20, 25, 32, 40, 50, 63, 80, 100
- Standard stroke range (mm): 5 to 100
- Port threads: M (12 to 25 bore); Rc, NPT or G (32 to 100 bore)
- Can mount small auto switches on 4 surfaces.

Magnet	D (Built-in)
Mounting	D (Double Clevis)
Type	Standard
Bore Size	Ø16 mm
Port Thread Type	Rc
Lube-retainer	Without Stable Lubrication Function
Stroke	25
Body Option	Standard [Rod End Female Thread]
Auto Switch Groove	None, also for 12-25 Bore w/o Magnet
Mounting Bolt	None
Rod End Bracket	None
Auto Switch	No Switch
Lead Wire or Prewired Connector	Z (5 m)
Number	2 pcs.
Rod End Options	None
Temperature Resistance	None
Low Speed	None
Made of Stainless Steel	None

Fluororubber Seal	None
-	Compressed air
Weight	0.133 Kg

二山クレビス形 / CQ2D



二山クレビス形

寸法 (mm)	寸法 (mm)	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z
12	5~30	45	17	12	5	34	4	7	14	5	10	15	14	14	14	14	14	14	14	14	14	14	14	14	14	14	
16	5~30	43	18	14	5	37	4	10	15	6	12	13	15	15	14	14	14	14	14	14	14	14	14	14	14	14	
20	5~50	51	19	20	8	42	5	12	18	8	16	14	16	16	15	15	14	14	14	14	14	14	14	14	14	14	
25	5~50	57	22	24	10	47	5	14	20	10	20	15	18	18	16	16	15	15	14	14	14	14	14	14	14	14	

二山クレビス金具材質：鋼製鋼
表面処理：ニッケルめっき

二山クレビス形は、標準品として、
お問い合わせください。

ロット番号をお知らせ



-

-

CQ2-Z-B_EU.pdf