




C(D)Q2, Compact Cylinder, Double Acting, Single Rod w/Auto Switch Mounting Groove CDQ2F50-100DZ

- Double acting, single rod, compact cylinder
- Bore sizes (mm): 12, 16, 20, 25, 32, 40, 50, 63, 80, 100
- Standard stroke range (mm): 5 to 100
- Port threads: M (12 to 25 bore); Rc, NPT or G (32 to 100 bore)
- Can mount small auto switches on 4 surfaces.

Magnet	D (Built-in)
Mounting	F (Front Flange)
Type	Standard
Bore Size	Ø50 mm
Port Thread Type	Rc
Lube-retainer	Without Stable Lubrication Function
Stroke	100
Body Option	Standard [Rod End Female Thread]
Auto Switch Groove	None, also for 12-25 Bore w/o Magnet
Mounting Bolt	None
Rod End Bracket	None
Auto Switch	No Switch
Lead Wire or Prewired Connector	Z (5 m)
Number	2 pcs.
Rod End Options	None
Temperature Resistance	None
Low Speed	None
Made of Stainless Steel	None

Fluororubber Seal	None
-	Compressed air
Weight	1.520 Kg



ボルト径 (mm)	ストローク調整 (mm)	ボルト径 (mm)		FD	FT	FV	FX	FZ	L	M			
		A	B										
32	75, 100	50	60	50	33	5.5	6	48	56	65	17	35.5	34
40	75, 100	50	60	50	33	5.5	6	54	62	72	17	38.5	40
50	75, 100	50	60	50	33	5.5	6	67	76	89	18	43.5	50

フランジ取付時間: 作業員
表面処理: ニッケルメッキ

-

-

CQ2-Z-B_EU.pdf