

C(D)Q2, Compact Cylinder, Double Acting, Single Rod w/Auto Switch Mounting Groove

CQ2D50-40DMZ

Datasheet


General series information

- Double acting, single rod, compact cylinder
- Bore sizes (mm): 12, 16, 20, 25, 32, 40, 50, 63, 80, 100
- Standard stroke range (mm): 5 to 100
- Port threads: M (12 to 25 bore); Rc, NPT or G (32 to 100 bore)
- Can mount small auto switches on 4 surfaces.

Standard specifications

Magnet	None
Mounting	D (Double Clevis)
Type	Standard
Bore Size	Ø50 mm
Port Thread Type	Rc
Lube-retainer	Without Stable Lubrication Function
Stroke	40
Body Option	M [Rod End Male Thread]
Auto Switch Groove	None, also for 12-25 Bore w/o Magnet
Mounting Bolt	None
Rod End Bracket	None
Auto Switch	No Switch
Lead Wire or Prewired Connector	Z (5 m)
Number	2 pcs.
Rod End Options	None
Temperature Resistance	None
Low Speed	None
Made of Stainless Steel	None
Fluororubber Seal	None
-	Compressed air

Dimensions



ニ山クレブシ形											(mm)
ナット径	ナット高	ボルト径				ボルト高					
		A	B	C	L	A	B	C	L	DO	CT
32	75.100	100	210	100	30	130	30	60	10	5	14
40	75.100	100	210	100	30	130	30	60	10	5	14
50	75.100	100	210	100	30	130	30	60	10	5	14
60	75.100	100	210	100	30	130	30	60	10	5	14
70	75.100	100	210	100	30	130	30	60	10	5	14
80	75.100	100	210	100	30	130	30	60	10	5	14
90	75.100	100	210	100	30	130	30	60	10	5	14
100	75.100	100	210	100	30	130	30	60	10	5	14
110	75.100	100	210	100	30	130	30	60	10	5	14
120	75.100	100	210	100	30	130	30	60	10	5	14
130	75.100	100	210	100	30	130	30	60	10	5	14
140	75.100	100	210	100	30	130	30	60	10	5	14
150	75.100	100	210	100	30	130	30	60	10	5	14
160	75.100	100	210	100	30	130	30	60	10	5	14
180	75.100	100	210	100	30	130	30	60	10	5	14
200	75.100	100	210	100	30	130	30	60	10	5	14
220	75.100	100	210	100	30	130	30	60	10	5	14
240	75.100	100	210	100	30	130	30	60	10	5	14
260	75.100	100	210	100	30	130	30	60	10	5	14
280	75.100	100	210	100	30	130	30	60	10	5	14
300	75.100	100	210	100	30	130	30	60	10	5	14
320	75.100	100	210	100	30	130	30	60	10	5	14
340	75.100	100	210	100	30	130	30	60	10	5	14
360	75.100	100	210	100	30	130	30	60	10	5	14
380	75.100	100	210	100	30	130	30	60	10	5	14
400	75.100	100	210	100	30	130	30	60	10	5	14
420	75.100	100	210	100	30	130	30	60	10	5	14
440	75.100	100	210	100	30	130	30	60	10	5	14
460	75.100	100	210	100	30	130	30	60	10	5	14
480	75.100	100	210	100	30	130	30	60	10	5	14
500	75.100	100	210	100	30	130	30	60	10	5	14
520	75.100	100	210	100	30	130	30	60	10	5	14
540	75.100	100	210	100	30	130	30	60	10	5	14
560	75.100	100	210	100	30	130	30	60	10	5	14
580	75.100	100	210	100	30	130	30	60	10	5	14
600	75.100	100	210	100	30	130	30	60	10	5	14
620	75.100	100	210	100	30	130	30	60	10	5	14
640	75.100	100	210	100	30	130	30	60	10	5	14
660	75.100	100	210	100	30	130	30	60	10	5	14
680	75.100	100	210	100	30	130	30	60	10	5	14
700	75.100	100	210	100	30	130	30	60	10	5	14
720	75.100	100	210	100	30	130	30	60	10	5	14
740	75.100	100	210	100	30	130	30	60	10	5	14
760	75.100	100	210	100	30	130	30	60	10	5	14
780	75.100	100	210	100	30	130	30	60	10	5	14
800	75.100	100	210	100	30	130	30	60	10	5	14
820	75.100	100	210	100	30	130	30	60	10	5	14
840	75.100	100	210	100	30	130	30	60	10	5	14
860	75.100	100	210	100	30	130	30	60	10	5	14
880	75.100	100	210	100	30	130	30	60	10	5	14
900	75.100	100	210	100	30	130	30	60	10	5	14
920	75.100	100	210	100	30	130	30	60	10	5	14
940	75.100	100	210	100	30	130	30	60	10	5	14
960	75.100	100	210	100	30	130	30	60	10	5	14
980	75.100	100	210	100	30	130	30	60	10	5	14
1000	75.100	100	210	100	30	130	30	60	10	5	14

Additional information

Catalogue

[CQ2-Z-B_EU.pdf](#)