

C(D)Q2, Compact Cylinder, Double Acting, Single Rod w/Auto Switch Mounting Groove

CQ2F32-20DZ

Datasheet


General series information

- Double acting, single rod, compact cylinder
- Bore sizes (mm): 12, 16, 20, 25, 32, 40, 50, 63, 80, 100
- Standard stroke range (mm): 5 to 100
- Port threads: M (12 to 25 bore); Rc, NPT or G (32 to 100 bore)
- Can mount small auto switches on 4 surfaces.

Standard specifications

Magnet	None
Mounting	F (Front Flange)
Type	Standard
Bore Size	Ø32 mm
Port Thread Type	Rc
Lube-retainer	Without Stable Lubrication Function
Stroke	20
Body Option	Standard [Rod End Female Thread]
Auto Switch Groove	None, also for 12-25 Bore w/o Magnet
Mounting Bolt	None
Rod End Bracket	None
Auto Switch	No Switch
Lead Wire or Prewired Connector	Z (5 m)
Number	2 pcs.
Rod End Options	None
Temperature Resistance	None
Low Speed	None
Made of Stainless Steel	None
Fluororubber Seal	None
-	Compressed air

Dimensions



ロッド端フランジ形

ロッド径 (mm)	F1 (mm)	F2 (mm)	L (mm)	L1 (mm)	L2 (mm)
12	20	15	10	10	10
16	25	20	15	15	15
20	30	25	20	20	20
25	35	30	25	25	25
32	40	35	30	30	30
40	50	45	40	40	40
50	60	55	50	50	50
63	75	70	60	60	60
80	90	85	75	75	75
100	110	105	90	90	90

フランジ取付時、油圧油
漏れ防止のため、
油圧油を漏れ防止剤
を塗布してください。

Additional information

Catalogue

[CQ2-Z-B_EU.pdf](#)