

# C(D)Q2, Compact Cylinder, Double Acting, Single Rod w/Auto Switch Mounting Groove

## CQ2F32-40DZ

### Datasheet


## General series information

- Double acting, single rod, compact cylinder
- Bore sizes (mm): 12, 16, 20, 25, 32, 40, 50, 63, 80, 100
- Standard stroke range (mm): 5 to 100
- Port threads: M (12 to 25 bore); Rc, NPT or G (32 to 100 bore)
- Can mount small auto switches on 4 surfaces.

## Standard specifications

|                                 |                                      |
|---------------------------------|--------------------------------------|
| Magnet                          | None                                 |
| Mounting                        | F (Front Flange)                     |
| Type                            | Standard                             |
| Bore Size                       | Ø32 mm                               |
| Port Thread Type                | Rc                                   |
| Lube-retainer                   | Without Stable Lubrication Function  |
| Stroke                          | 40                                   |
| Body Option                     | Standard [Rod End Female Thread]     |
| Auto Switch Groove              | None, also for 12-25 Bore w/o Magnet |
| Mounting Bolt                   | None                                 |
| Rod End Bracket                 | None                                 |
| Auto Switch                     | No Switch                            |
| Lead Wire or Prewired Connector | Z (5 m)                              |
| Number                          | 2 pcs.                               |
| Rod End Options                 | None                                 |
| Temperature Resistance          | None                                 |
| Low Speed                       | None                                 |
| Made of Stainless Steel         | None                                 |
| Fluororubber Seal               | None                                 |
| -                               | Compressed air                       |

# Dimensions



ロッド端フランジ形

| フランジ径 (mm) | F1 (mm) | F2 (mm) | L (mm) | L1 (mm) | L2 (mm) |
|------------|---------|---------|--------|---------|---------|
| 32         | 40      | 50      | 17     | 20      | 14      |
| 40         | 50      | 60      | 20     | 25      | 18      |
| 50         | 60      | 70      | 25     | 30      | 22      |
| 60         | 70      | 80      | 30     | 35      | 28      |
| 80         | 90      | 100     | 40     | 45      | 38      |
| 100        | 110     | 120     | 50     | 55      | 48      |

フランジ径単位:mm 標準寸法  
単位:mm 標準寸法

## Additional information

Catalogue

[CQ2-Z-B\\_EU.pdf](#)