





C(D)Q2, Compact Cylinder, Double Acting, Single Rod w/Auto Switch Mounting Groove CQ2L50-100DMZ

- Double acting, single rod, compact cylinder
- Bore sizes (mm): 12, 16, 20, 25, 32, 40, 50, 63, 80, 100
- Standard stroke range (mm): 5 to 100
- Port threads: M (12 to 25 bore); Rc, NPT or G (32 to 100 bore)
- Can mount small auto switches on 4 surfaces.

Magnet	None
Mounting	L (Foot)
Type	Standard
Bore Size	Ø50 mm
Port Thread Type	Rc
Lube-retainer	Without Stable Lubrication Function
Stroke	100
Body Option	M [Rod End Male Thread]
Auto Switch Groove	None, also for 12-25 Bore w/o Magnet
Mounting Bolt	None
Rod End Bracket	None
Auto Switch	No Switch
Lead Wire or Prewired Connector	Z (5 m)
Number	2 pcs.
Rod End Options	None
Temperature Resistance	None
Low Speed	None
Made of Stainless Steel	None

Fluororubber Seal	None
-	Compressed air

フート形/CQ2L・CDQ2L



フート形

フート形										(mm)									
ボア	スロー	スロー	スロー	スロー	スロー	スロー	スロー	スロー	スロー	スロー	スロー	スロー	スロー	スロー	スロー	スロー	スロー	スロー	スロー
	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S
32	76	100	125	150	175	200	225	250	275	300	325	350	375	400	425	450	475	500	525
40	76	100	125	150	175	200	225	250	275	300	325	350	375	400	425	450	475	500	525
50	76	100	125	150	175	200	225	250	275	300	325	350	375	400	425	450	475	500	525

フート全長単位: 100mm
表面処理: ニッケルめっき

-
-

CQ2-Z-B_EU.pdf