





## C(D)Q2K, Compact Cylinder, Double Acting, Single Rod, Non-rotating w/Auto Switch Mounting Groove CDQ2KA50-25DMZ

Datasheet

### General series information

- Double acting, single rod, non-rotating compact cylinder
- Bore sizes (mm): 12, 16, 20, 25, 32, 40, 50, 63
- Standard stroke range (mm): 5 to 100
- Port threads: M (12 to 25 bore); Rc, NPT or G (32 to 63 bore)
- Can mount small auto switches on 4 surfaces.




Double-acting, single-rod cylinder

### Standard specifications


|                                        |                                                       |
|----------------------------------------|-------------------------------------------------------|
| Magnet                                 | D (Built-in)                                          |
| Mounting                               | A (Both Ends Tapped; 40 Through 63 Bore)              |
| Bore Size                              | Ø50 mm                                                |
| Port Thread                            | Rc (or M Thread for 16 and 20 Bore or 32 stroke 5 mm) |
| Stroke                                 | 25                                                    |
| Body Option                            | M (Rod End Male Thread)                               |
| Auto Switch Groove                     | Z [Auto Switch Mounting Grooves]                      |
| Auto Switch                            | No Switch                                             |
| Lead Wire or Pre-wired Connector       | 0.5 m (Or None in the Case of No Switch)              |
| Number                                 | 2 pcs.                                                |
| Rod End Options                        | None                                                  |
| Pressure medium                        | Compressed air                                        |
| Maximum temperature of pressure medium | 60 °C                                                 |
| Minimum temperature of pressure medium | -10 °C [without condensation]                         |
| Maximum operating pressure             | 1.0 MPa                                               |
| Minimum operating pressure             | 0,05 MPa                                              |
| Proof pressure                         | 1.5 MPa                                               |
| Maximum ambient temperature            | 60 °C                                                 |

|                                                         |                               |
|---------------------------------------------------------|-------------------------------|
| Minimum ambient temperature                             | -10 °C [without condensation] |
| Number of pneumatic connections                         | 2 pcs.                        |
| Pneumatic input connection                              | Rc 1/4                        |
| Mode of operation of drive                              | Double acting                 |
| Theoretical cylinder force, advance stroke (at 0.5 MPa) | 982 N                         |
| Theoretical cylinder force, return stroke (at 0.5 MPa)  | 825 N                         |
| Maximum piston speed                                    | 500 mm/s                      |
| Geometric form of the piston rod                        | Single rod                    |
| Male thread of rod end                                  | M18 x 1.5                     |
| Female thread of rod end                                | M10 x 1.5                     |
| Minimum piston speed                                    | 50 mm/s                       |




## Constructions


ø12 to ø25



ø32



ø40 to ø63



### Component Parts

| No. | Description                   | Material                       | Note                           |
|-----|-------------------------------|--------------------------------|--------------------------------|
| 1   | Cylinder tube                 | Aluminum alloy                 | Hard anodised                  |
| 2   | Piston                        | Aluminum alloy                 | Chromated                      |
| 3   | Piston rod                    | Stainless steel                | ø12 to ø25                     |
|     |                               | Carbon steel                   | ø32 to ø63, Hard chrome plated |
|     |                               | Brass                          | ø12, Electroless nickel plated |
| 4   | Rod cover                     | Aluminum alloy                 | ø16 to ø32, Anodised           |
|     |                               | Aluminum alloy                 | ø40 to ø63, Anodised           |
| 5   | Collar                        | Aluminum alloy                 | ø40 to ø63, Anodised           |
| 6   | Retaining ring                | Carbon tool steel              | Phosphate coated               |
| 7   | Bushing                       | Oil-impregnated sintered alloy | ø16 to ø63                     |
| 8   | Hexagon socket head cap screw | Alloy steel                    | ø12 to ø25, Nickel plated      |
| 9   | Hexagon socket head cap screw | Alloy steel                    | ø32, Nickel plated             |
| 10  | Hexagon socket head set screw | Alloy steel                    | ø40 to ø63, Nickel plated      |
| 11  | Magnet                        | —                              |                                |
| 12  | Piston seal                   | NBR                            |                                |
| 13  | Rod seal                      | NBR                            |                                |
| 14  | Tube gasket                   | NBR                            |                                |

## Additional information

Catalogue

[CQ2-Z-D\\_EU.pdf](#)

Operation manuals

[OM\\_CQ2x\\_OM0002MEN.pdf](#)