





C(D)RBU2*10~40-Z, Rotary Actuator, Free Mount, Vane Type CDRBU2W20-90DZ

Datasheet

- Free mount type.
- 12% weight reduction.
- Possible to move the plate mounting position as desired.
- Many mounting variations.




Semi-rotary actuator, double acting

Standard specifications

Magnet	D (Built-in)
Shaft Type	W (Double Shaft with Single Flat)
Size	20 mm
Rotating Angle	90 (90°)
Vane Type	D (Double Vane)
Connecting Port Location	Side Ported
Auto Switch	No Switch
Electrical Entry/Lead Wire Length	0.5m
Number	2 pcs.
-	Air (Non-lube)
Maximum operating pressure	0.7 MPa
Minimum operating pressure	0.15 MPa
Pneumatic input connection	M5 x 0.8
Pneumatic exhaust connection	M5 x 0.8
Theoretical cylinder force, advance stroke (at 0.5 MPa)	1.05 N
Rotation time adjustment range s/90°	0.03 to 0.3
Shaft load: Allowable radial load	25 N
Shaft load: Allowable thrust load	20 N
Weight	0.173 Kg

Dimensions




Constructions

Double vane • Figures below show the intermediate rotation position when A or B port is pressurised.

Size: 10



For 90°

(Viewed from the output shaft side)




For 100°

(Viewed from the output shaft side)



Single shaft type




Double shaft type

Size: 15, 20, 30, 40



For 90°

(Viewed from the output shaft side)




For 100°

(Viewed from the output shaft side)



Single shaft type



Double shaft type

Component Parts

No.	Description	Material	Note
1	Body (A)	Aluminium alloy	Painted
2	Body (B)	Aluminium alloy	Painted
3	Vane shaft	Chrome molybdenum	
4	Stopper	Stainless steel ^{*1}	
5	Stopper	Resin	
6	Stopper	Stainless steel ^{*1}	
7	Bearing	Bearing steel	
8	Back-up ring	Stainless steel	
9	Cover	Aluminium alloy	
10	Plate	Resin	

*1. For size 40, material for (4), (6) is aluminum alloy.

*2. Hexagon socket flat countersunk head cap screw is used for size 10. (19) and (20) are shipped with the product for all sizes, and special mounting screws (M3 x 12) are attached for size 10.

No.	Description	Material	Note
11	Hexagon socket head cap screw	Chrome molybdenum	Special screw
12	O-ring	NBR	
13	Stopper seal	NBR	Special seal
14	Gasket	NBR	Special seal
15	O-ring	NBR	
16	O-ring	NBR	
17	O-ring	NBR	Size 40 only
18	Parallel key	Carbon steel	Size 40 only
19	Plate	Aluminium alloy	Anodised
20	Hexagon socket head cap screw ^{*2}	Chrome molybdenum	Special screw for size

Additional information

Catalogue

[CRB2-C_EU.pdf](#)