

C96S(D) ø125, ISO Cylinder, Double Acting, Single/Double Rod C96SDT125-1400

Datasheet


- Double acting, standard type, single or double rod
- Bore sizes (mm): 125
- Maximum stroke 2000mm
- Auto switch capable

Standard specifications


Magnet	D (Built-in)
Mounting	T (Centre Trunnion)
Bore Size	125mm
Stroke	1400
Rod Boot	None
Rod	Single Rod
Auto Switch	No Switch
Lead Wire or Prewired Connector	0.5m [Or None in the Case of No Switch]
Number	2 pcs. [Or None in the Case of No Switch]
Rod End Options	None
Temperature Resistance	None
Heavy Duty Scraper	None
Tie Rod	None
Fluororubber Seal	None
Made of Stainless Steel (-XC68)	None
Made of Stainless Steel (-XC65)	None
-	Compressed Air
Maximum operating pressure	1.0 MPa
Minimum operating pressure	0.05 MPa
Proof pressure	1.5 MPa

Pneumatic input connection	G 1/2
Pneumatic output connection	G 1/2
Maximum piston speed	700 mm/s
Type of cushioning	Both Ends (Air Cushion)
Piston rod end	Male thread
Male thread of rod end	M27 x 2
Weight	25.550 Kg


Dimensions



With rod boot

[illegible]

Dimensions: Cylinder Mounting Accessories *First angle projection*



Additional information

Catalogue

[C96-Bb_EU.pdf](#)