




## KK\*S-\*M, S-Couplers, Male Thread KK2S-M5M

Datasheet


### General series information


- Male thread.
- Body size: M5, 1/8, 1/4, 1/2.
- Applicable Port Size: M5, R1/8, R1/4, R3/8, R1/2, R3/4.

### Standard specifications

|                             |                                                                               |
|-----------------------------|-------------------------------------------------------------------------------|
| Body Size                   | 2 (M5)                                                                        |
| Piping Port Size            | M5x0.8                                                                        |
| Sealant                     | None                                                                          |
| Pressure medium             | Air, Water                                                                    |
| Maximum operating pressure  | 1.0 MPa                                                                       |
| Minimum operating pressure  | -100 kPa                                                                      |
| Proof pressure              | 1.5 MPa                                                                       |
| Maximum ambient temperature | 60 °C / 40 °C for Water                                                       |
| Minimum ambient temperature | -5 °C (with no freezing) / 5 °C for Water                                     |
| Effective Area              | 3.8 mm <sup>2</sup>                                                           |
| Sealing principle           | Electroless nickel plated (copper-free application), With male thread sealant |
| Weight                      | 0.006 Kg                                                                      |

## Dimensions





## Additional information

Catalogue

[KK-C\\_EU.pdf](#)