



MXQ*Z, Air Slide Table, Height Interchangeable Type MXQ16-125ZG

Datasheet


General series information

- Mounting: Interchangeable in mounting with the conventional model.
- Height: Same height as the conventional model.
- Lighter: Weight reduced up to 31%.
- Auto switch visibility improved.

Standard specifications

Bore Size	16 mm
Body Option	Standard
Stroke	125 mm
Adjuster Option	ZG [Shock Absorber (Extension Stroke End + Retraction Stroke End)]
Functional Option	Without Functional Option
Auto Switch	No Switch
Lead Wire or Prewired Connector	0.5m (Or None in the Case of No Switch)
Number	2 pcs. (Or None in the Case of No Switch)
Made to Order	None
Side Adjuster Position	None (or Standard Type)
Pressure medium	Compressed air
Maximum temperature of pressure medium	60 °C
Minimum temperature of pressure medium	-10 °C
Maximum operating pressure	0.7 MPa
Minimum operating pressure	0.15 MPa
Proof pressure	1.05 MPa
Maximum ambient temperature	60 °C
Minimum ambient temperature	-10 °C

Number of pneumatic connections	2 pcs.
Pneumatic input connection	M5 x 0.8
Mode of operation of drive	Double acting
Theoretical cylinder force, advance stroke (at 0.5 MPa)	201 N
Theoretical cylinder force, return stroke (at 0.5 MPa)	173 N
Maximum piston speed	500 mm/s
Type of cushioning	Shock absorber
Weight	1.390 Kg



Additional information

Catalogue	MXQ-Z-C_EU.pdf
Operation manuals	OM_MXQ-Z_OMP0038EN-D.pdf