

Pressure Gauge MA-50-2,5-1/4-EN - Festo 162837

Item no. FES-162837

Manufacturer Festo

EAN 4052568036614

Festo pneumatic component for industrial automation and compressed-air applications in proven quality.

TECHNICAL DATA

Betriebsdruck max [bar]	2.500000
Pneumatischer Anschluss	G1/4
Schutzart	IP43
Weight	0.085 kg
Zolltarifnummer	90262040



DESCRIPTION

Festo pneumatic component for industrial automation and compressed-air applications in proven quality. The key technical data of this genuine Festo article are listed below.

Display range [bar] [bar]	0 to 2.5
Nominal size pressure gauge	50
Construction set up	Pipe spring pressure gauge
Fastening type	pipe installation
Operating medium	Inert gases Neutral liquids
Operating pressure [bar]	0 to 2.5
Factor alternating strain	0.66
Measurement precision class	2,5
Protection category	IP43
Medium temperature [°C]	-20 to 60
ambient temperature [°C]	-20 to 60
Material information	RoHs compliant
Connection position	Back side centred
Pneumatic connection	G1/4

A1-ESD equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com
fluidics-equipment.com

Page 1/2

Stud material	Brass
Housing material	ABS
Window material	PS
Housing colour	 black
Product weight [g]	70
Information about operating and control medium	No acetylene No oxygen
From medium contacting materials	Brass
Complies to standard	EN 837-1