

And Gate ZK-1/8-B - Festo 6680

Item no. FES-6680

Manufacturer Festo

EAN 4052568001285

Festo pneumatic component for industrial automation and compressed-air applications in proven quality.

TECHNICAL DATA

Betriebsdruck max [bar]	10.000000
Flow rate [l/min]	550
Function	AND function
Material	Aluminium
Medium	Compressed air
Mounting position	arbitrary
Nominal size DN [mm]	4,5
Pneumatic connection	G1/8
Seal material	NBR
Temperature (max.)	60
Weight	0.046 kg
Zolltarifnummer	84812090



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo pneumatic component for industrial automation and compressed-air applications in proven quality. The key technical data of this genuine Festo article are listed below.

Valve function	AND function
Pneumatic connection 1	G1/8
Pneumatic connection 2	G1/8
Fastening type	With throughway bores
Normal nominal flow [l/min]	550
Operating pressure [bar]	1 to 10
ambient temperature [°C]	-10 to 60
Housing material	Aluminium wrought alloy anodized
Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-]
Nominal width [mm]	4,5
installation position	arbitrary

A1-ESD equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com
fluidics-equipment.com

Page 1/2

Information about operating and control medium	Oiled operation possible (required in further operations)
Medium temperature [°C]	-10 to 60
Product weight [g]	45
Pneumatic connection 3	G1/8
Seals material	NBR
Material information	RoHs compliant