

## C(D)85, ISO Standard Cylinder, Double Acting, Single Rod - SMC CD85N12-160C-A

Item no. SMC-CD85N12-160C-A

Manufacturer SMC

Magnet: D (Built-in) Mounting: N (Basic Integrated Clevis) Bore Size: Ø12 mm Stroke: 160 Cushion: C (Air Cushion) Rod Boot: None Auto Switch Mounting Type: A (Rail) Auto Switch: No Switch Lead Wire or Prewired Connector: 0.5m (Or None in the Case of No Switch) Number: 2 pcs. (Or None in the Case of No Switch) Rod End Options: None Temperature Resistance: None Low Speed: None Stainless Steel: None Long Stroke: None

### TECHNICAL DATA

|                 |                 |
|-----------------|-----------------|
| Certification   | <b>ATEX</b>     |
| Norm            | <b>ISO 6432</b> |
| Weight          | <b>0.16 kg</b>  |
| Zolltarifnummer | <b>84123100</b> |



## STANDARDS & COMPLIANCE

ISO 6432

### DESCRIPTION

- ISO 6432 Round Body Cylinder.
- Bore sizes (mm): 8, 10, 12, 16, 20, 25.
- Standard strokes up to 300 mm.
- Cylinder variations: Non-rotating, direct mount, ATEX.