

VP700, 3 Port Pilot Operated Poppet - SMC

VP742K-5YOSD1-04FA

Item no. SMC-VP742K-5YOSD1-04FA

Manufacturer SMC

Body Style: 2 (Body Ported) Valve Option: Standard (Internal pilot)
 Pressure Specification: K [High-pressure type (1.0 MPa)] Coil
 Specification: Standard Rated Voltage: 5 (24V DC) Electrical
 Entry: YO [DIN terminal, Without connector (EN175301-803)]
 Light and Surge Voltage Suppressor: S (With surge voltage
 suppressor) Manual Override: D (Push-turn Locking Slotted Type)
 Port Size: 04 (1/2) Thread: F [G (PF)] Actuation: A (Normally
 closed) Option: None Made to Order: None

TECHNICAL DATA

Norm	EN 175301-803
Weight	0.1 kg
Zolltarifnummer	84812090



STANDARDS & COMPLIANCE

EN175301-803

DESCRIPTION

High flow capacity: Cv1.0 (VP300), Cv2.3 (VP500), Cv4.0 (VP700). Low power consumption: 1.8W(DC). Possible to use as either selector valve or divider valve. Changeable from normally closed style to normally open style. Vacuum applicable: Up to -101.2kPa.