

5/2-Directional Control Valve, monostable Mini ISO 24Vdc - Norgren VS26S527DF313A

Item no. NRG-VS26S527DF313A

Manufacturer Norgren

5/2-Wv-Mono Mini Iso 24Vdc. Norgren pneumatic valve controls the direction and flow of compressed air to the actuators.

TECHNICAL DATA

Norm	ISO 15407-2
Weight	0.22 kg
Zolltarifnummer	84812090



DESCRIPTION

Norgren pneumatic valve controls the direction and flow of compressed air to the actuators. Fast, reliable switching for dynamic automation.

TECHNICAL DATA

BetriebsMedium	Druckluft
Ambient temperature	-15 ... 50 °C
Operating Temperaturee	5 ... 122 °F
Pressure range	1.6 ... 10 bar
Operating Pressure	29 ... 145 psi
Norm	ISO 15407-2
Actuation	Spule / Feder
Function	5/2
Zertifikate - WEEE	WEEE
Klassifikation - eClass 11	51030100
Series	VS26
Series	VS26

A1-ESD equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com
fluidics-equipment.com

Page 1/2

VERSION

5/2-Wv-Mono Mini Iso 24Vdc.

MANUFACTURER

Genuine Norgren.