

Tie Rod Mini Cylinder, double-acting - Norgren RA/802050/M/125

Item no. NRG-RA/802050/M/125

Manufacturer Norgren

double-acting ZSTG-MZYL. Norgren pneumatic cylinder converts compressed air into linear motion and force.

TECHNICAL DATA

Weight	1.7 kg
Zolltarifnummer	84123100



DESCRIPTION

Norgren pneumatic cylinder converts compressed air into linear motion and force. Rugged design for precise, reliable working strokes in automation.

TECHNICAL DATA

BetriebsMedium	Compressed air filtered and lubricated or non-lubricated
Ambient temperature	-20 ... 80 °C
Operating Temperaturee	-4 ... 176 °F
Pressure range	1 ... 16 bar
Operating Pressure	14 ... 232 psi
Norm	ISO 15552
Port	G1/4
Zylinderdurchmesser	50 mm
BestellStroke	125 mm
Function	Doppelwirkend
Cushioning	Adaptive Cushioning System (ACS)
Magnetic/Non-magnetic	Magnetisch

Theoretical Force	1178 N
Materials - Barrel	Eloxiertes Aluminium
Material - Kolbendichtung	PUR
Material - Kolbenstange	Stainless steel (martensitic)
Zertifikate - REACH	Lieferbar auf Anfrage
Zertifikate - RoHS-konform	Lieferbar auf Anfrage
Zertifikate - WEEE	NonWEEE
Klassifikation - eClass 11	51010101
Klassifikation - HS-Code (Zoll)	84123100
Klassifikation - HTS-Code (Harmonisierter Zolltarifplan)	8412310000
Klassifikation - MIL Spec	Nicht verfügbar
Klassifikation - UNSPSC-Code	27131701
Klassifikation - US-Exportkontroll-Klassifizierungsnummer (ECCN)	EAR99
Produkt - Höhe	66 mm
Produkt - Länge	178 mm
Produkt - Breite	66 mm
Weight	1.21 kg
Series	RA/802000/M
Series	ISOLine
Marken	Norgren

VERSION

double-acting ZSTG-MZYL.

MANUFACTURER

Genuine Norgren.