

Compact Mini Cylinder, double-acting - Norgren RA/192040/M/40

Item no. NRG-RA/192040/M/40

Manufacturer Norgren

Dw Kompakt-Mzyl. Norgren pneumatic cylinder converts compressed air into linear motion and force.

TECHNICAL DATA

Norm	ISO 21287
Weight	0.46 kg
Zolltarifnummer	84123100



DESCRIPTION

Norgren pneumatic cylinder converts compressed air into linear motion and force. Rugged design for precise, reliable working strokes in automation.

TECHNICAL DATA

BetriebsMedium	Druckluft
Ambient temperature	-5 ... 80 °C
Pressure range	1 ... 10 bar
Norm	ISO 21287
Port	G1/8
Zylinderdurchmesser	40 mm
BestellStroke	40 mm
Function	Doppelwirkend
Cushioning	Endlagenpuffer
Magnetic/Non-magnetic	Magnetisch
Theoretical Force	754 N
Materials - Barrel	Eloxiertes Aluminium

A1-ESD equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com
fluidics-equipment.com

Material - Elastomere	Nitrile rubber
Material - Kolbendichtung	Nitril
Material - Kolbenstange	Rostfreier Stahl (martinitisch)
Zertifikate - RoHS-konform	Lieferbar auf Anfrage
Zertifikate - WEEE	NonWEEE
Klassifikation - eClass 11	51010103
Klassifikation - HS-Code (Zoll)	84123100
Klassifikation - US-Exportkontroll-Klassifizierungsnummer (ECCN)	EAR99
Series	RA/192000/M
Series	ISO Compact
Marken	Norgren

VERSION

Dw Kompakt-Mzyl.

MANUFACTURER

Genuine Norgren.