

Double-acting Round Cylinder - Norgren RT/57232/M/160

Item no. NRG-RT/57232/M/160

Manufacturer Norgren

Double-acting Round Cylinder. Norgren pneumatic cylinder converts compressed air into linear motion and force.

TECHNICAL DATA

Weight	0.45 kg
Zolltarifnummer	84123100



DESCRIPTION

Norgren pneumatic cylinder converts compressed air into linear motion and force. Rugged design for precise, reliable working strokes in automation.

TECHNICAL DATA

BetriebsMedium	Druckluft
Ambient temperature	-10 ... 80 °C
Pressure range	1 ... 10 bar
Port	Rc1/8
Zylinderdurchmesser	32 mm
BestellStroke	160 mm
Function	Doppelwirkend
Cushioning	Endlagenpuffer
Magnetic/Non-magnetic	Magnetisch
Theoretical Force	414 N
Materials - Barrel	material stainless steel (austenitic)
Material - Kolbenstange	Stainless steel (martensitic)

Zertifikate - REACH	Lieferbar auf Anfrage
Zertifikate - RoHS-konform	Lieferbar auf Anfrage
Zertifikate - WEEE	NonWEEE
Klassifikation - eClass 11	51010102
Klassifikation - HS-Code (Zoll)	84123100
Klassifikation - HTS-Code (Harmonisierter Zollltarifplan)	8412310000
Klassifikation - MIL Spec	Nicht verfügbar
Klassifikation - UNSPSC-Code	27131701
Klassifikation - US-Exportkontroll-Klassifizierungsnummer (ECCN)	EAR99
Produkt - Länge	283 mm
Weight	1.234 kg
Series	RT/57200/M
Series	Roundline
Marken	Norgren

VERSION

double-acting Round Cylinder.

MANUFACTURER

Genuine Norgren.

A1-ESD equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com
fluidics-equipment.com

Page 2/2