

Double-acting Compact Cylinder - Norgren RM/92050/M/40

Item no. NRG-RM/92050/M/40

Manufacturer Norgren

Double-acting Compact Cylinder. Norgren pneumatic cylinder converts compressed air into linear motion and force.

TECHNICAL DATA

Weight	0.65 kg
Zolltarifnummer	84123100



DESCRIPTION

Norgren pneumatic cylinder converts compressed air into linear motion and force. Rugged design for precise, reliable working strokes in automation.

TECHNICAL DATA

BetriebsMedium	Druckluft
Ambient temperature	-5 ... 80 °C
Operating Temperaturee	23 ... 176 °F
Pressure range	1 ... 10 bar
Operating Pressure	14 ... 145 psi
Port	G1/8
Zylinderdurchmesser	50 mm
BestellStroke	40 mm
Cushioning	Keine Endlagendämpfung
Magnetic/Non-magnetic	Magnetisch
Theoretical Force	990 N
Materials - Barrel	Eloxierte Aluminiumlegierung

Material - Kolbenstange	Rostfreier Stahl (martinitisch)
Material - Dichtungen	Polyurethan
Zertifikate - REACH	Lieferbar auf Anfrage
Zertifikate - RoHS-konform	Lieferbar auf Anfrage
Zertifikate - WEEE	NonWEEE
Klassifikation - eClass 11	51010103
Klassifikation - HS-Code (Zoll)	84123100
Klassifikation - HTS-Code (Harmonisierter Zolltarifplan)	8412310000
Klassifikation - MIL Spec	Nicht verfügbar
Klassifikation - UNSPSC-Code	27131701
Klassifikation - US-Exportkontroll-Klassifizierungsnummer (ECCN)	EAR99
Produkt - Höhe	68.5 mm
Produkt - Länge	83 mm
Produkt - Breite	63 mm
Weight	1.89 kg
Series	RM/92000/M
Marken	Norgren

VERSION

double-acting Compact Cylinder.

MANUFACTURER

Genuine Norgren.