

Double-acting Compact Cylinder - Norgren RM/92040/M/25

Item no. NRG-RM/92040/M/25

Manufacturer Norgren

Double-acting Compact Cylinder. Norgren pneumatic cylinder converts compressed air into linear motion and force.

TECHNICAL DATA

Weight	0.37 kg
Zolltarifnummer	84123100



DESCRIPTION

Norgren pneumatic cylinder converts compressed air into linear motion and force. Rugged design for precise, reliable working strokes in automation.

TECHNICAL DATA

BetriebsMedium	Druckluft
Ambient temperature	-5 ... 80 °C
Operating Temperaturee	23 ... 176 °F
Pressure range	1 ... 10 bar
Operating Pressure	14 ... 145 psi
Port	G1/8
Zylinderdurchmesser	40 mm
BestellStroke	25 mm
Cushioning	Keine Endlagendämpfung
Magnetic/Non-magnetic	Magnetisch
Theoretical Force	633 N
Materials - Barrel	Eloxierte Aluminiumlegierung

Material - Kolbenstange	Rostfreier Stahl (austenitisch)
Material - Dichtungen	Polyurethan
Zertifikate - REACH	Lieferbar auf Anfrage
Zertifikate - RoHS-konform	Lieferbar auf Anfrage
Zertifikate - WEEE	NonWEEE
Klassifikation - eClass 11	51010103
Klassifikation - HS-Code (Zoll)	84123100
Klassifikation - HTS-Code (Harmonisierter Zolllarifplan)	8412310000
Klassifikation - MIL Spec	Nicht verfügbar
Klassifikation - UNSPSC-Code	27131701
Klassifikation - US-Exportkontroll-Klassifizierungsnummer (ECCN)	EAR99
Produkt - Höhe	59 mm
Produkt - Länge	63 mm
Produkt - Breite	55 mm
Weight	1.13 kg
Series	RM/92000/M
Marken	Norgren

VERSION

double-acting Compact Cylinder.

MANUFACTURER

Genuine Norgren.