

Double-acting Compact Cylinder - Norgren RM/92016/M/35

Item no. NRG-RM/92016/M/35

Manufacturer Norgren

Double-acting Compact Cylinder. Norgren pneumatic cylinder converts compressed air into linear motion and force.

TECHNICAL DATA

Weight	0.11 kg
Zolltarifnummer	84123100



DESCRIPTION

Norgren pneumatic cylinder converts compressed air into linear motion and force. Rugged design for precise, reliable working strokes in automation.

TECHNICAL DATA

BetriebsMedium	Druckluft
Ambient temperature	-5 ... 80 °C
Operating Temperaturee	23 ... 176 °F
Pressure range	1 ... 10 bar
Operating Pressure	14 ... 145 psi
Port	M5
Zylinderdurchmesser	16 mm
BestellStroke	35 mm
Cushioning	Keine Endlagendämpfung
Magnetic/Non-magnetic	Magnetisch
Theoretical Force	90 N
Materials - Barrel	Eloxierte Aluminiumlegierung

Material - Kolbenstange	Rostfreier Stahl (austenitisch)
Material - Dichtungen	Polyurethan
Series	RM/92000/M
Marken	Norgren

VERSION

double-acting Compact Cylinder.

MANUFACTURER

Genuine Norgren.