

Double-acting Profile Cylinder - Norgren RA/8320/M/320

Item no. NRG-RA/8320/M/320

Manufacturer Norgren

Double-acting Profile Cylinder. Norgren pneumatic cylinder converts compressed air into linear motion and force.

TECHNICAL DATA

Weight	2.2 kg
Zolltarifnummer	84123100



DESCRIPTION

Norgren pneumatic cylinder converts compressed air into linear motion and force. Rugged design for precise, reliable working strokes in automation.

TECHNICAL DATA

BetriebsMedium	Druckluft
Ambient temperature	-10 ... 80 °C
Pressure range	1 ... 10 bar
Norm	NFE 49-003-1
Port	G1
Zylinderdurchmesser	320 mm
BestellStroke	320 mm
Function	Doppelwirkend
Cushioning	Einstellbare Endlagendämpfung
Magnetic/Non-magnetic	Magnetisch
Theoretical Force	48228 N
Materials - Barrel	Eloxiertes Aluminium

A1-ESD equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com
fluidics-equipment.com

Page 1/2

Material - Elastomere	Nitrile rubber
Material - Kolbendichtung	Polyurethan
Material - Kolbenstange	Rostfreier Stahl (martinitisch) (1.4021)
Series	RA/8000/M
Series	ISO/VDMA Actuator
Marken	Norgren

VERSION

double-acting Profile Cylinder.

MANUFACTURER

Genuine Norgren.