

Tie Rod Mini Cylinder, double-acting - Norgren RA/8200/M/500

Item no. NRG-RA/8200/M/500

Manufacturer Norgren

Dw Zstg-Mzyl. Norgren pneumatic cylinder converts compressed air into linear motion and force.

TECHNICAL DATA

Weight	34 kg
Zolltarifnummer	84123100



DESCRIPTION

Norgren pneumatic cylinder converts compressed air into linear motion and force. Rugged design for precise, reliable working strokes in automation.

TECHNICAL DATA

BetriebsMedium	Druckluft
Ambient temperature	-10 ... 80 °C
Pressure range	1 ... 16 bar
Norm	NFE 49-003-1
Port	G3/4
Zylinderdurchmesser	200 mm
BestellStroke	500 mm
Function	Doppelwirkend
Cushioning	Einstellbare Endlagendämpfung
Magnetic/Non-magnetic	Magnetisch
Theoretical Force	18840 N
Materials - Barrel	Eloxiertes Aluminium

A1-ESD equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com
fluidics-equipment.com

Material - Elastomere	Nitrile rubber
Material - Kolbendichtung	Polyurethan
Material - Kolbenstange	Rostfreier Stahl (martinitisch) (1.4021)
Zertifikate - REACH	Lieferbar auf Anfrage
Zertifikate - RoHS-konform	Lieferbar auf Anfrage
Zertifikate - WEEE	NonWEEE
Klassifikation - eClass 11	51010101
Klassifikation - HS-Code (Zoll)	84123100
Klassifikation - HTS-Code (Harmonisierter Zolltarifplan)	8412310000
Klassifikation - MIL Spec	Nicht verfügbar
Klassifikation - UNSPSC-Code	27131701
Klassifikation - US-Exportkontroll-Klassifizierungsnummer (ECCN)	EAR99
Produkt - Höhe	224 mm
Produkt - Länge	847 mm
Produkt - Breite	224 mm
Weight	33.7 kg
Series	RA/8000/M
Series	ISO/VDMA Actuator
Marken	Norgren

VERSION

Dw Zstg-Mzyl.

MANUFACTURER

Genuine Norgren.