

Tie Rod Mini Cylinder, double-acting - Norgren RM/940/M/600

Item no. NRG-RM/940/M/600

Manufacturer Norgren

Dw Zstg-Mzyl. Norgren pneumatic cylinder converts compressed air into linear motion and force.

TECHNICAL DATA

Weight	0.1 kg
Zolltarifnummer	84123100



DESCRIPTION

Norgren pneumatic cylinder converts compressed air into linear motion and force. Rugged design for precise, reliable working strokes in automation.

TECHNICAL DATA

BetriebsMedium	Druckluft
Ambient temperature	-20 ... 80 °C
Pressure range	2 ... 10 bar
Port	G3/8
Zylinderdurchmesser	4"
BestellStroke	600 mm
Cushioning	Einstellbare Endlagendämpfung
Magnetic/Non-magnetic	Magnetisch
Theoretical Force	4420 N
Materials - Barrel	Eloxierte Aluminiumlegierung
Material - Lager	Aluminium-Druckguss
Material - Elastomere	Nitrile rubber

A1-ESD equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com
fluidics-equipment.com

Page 1/2

Material - Kolbenstange	Rostfreier Stahl (martenitisch)
Material - Kolben	Aluminium-Druckguss
Series	RM/900
Series	Martonair
Marken	Norgren

VERSION

Dw Zstg-Mzyl.

MANUFACTURER

Genuine Norgren.