

Double-acting P-Cylinder - Norgren RM/960/750

Item no. NRG-RM/960/750

Manufacturer Norgren

Dw P-Zyl.. Norgren pneumatic cylinder converts compressed air into linear motion and force.

TECHNICAL DATA

Weight	0.1 kg
Zolltarifnummer	84123100



DESCRIPTION

Norgren pneumatic cylinder converts compressed air into linear motion and force. Rugged design for precise, reliable working strokes in automation.

TECHNICAL DATA

BetriebsMedium	Druckluft
Ambient temperature	-20 ... 80 °C
Pressure range	2 ... 10 bar
Port	G1/2
Zylinderdurchmesser	5"
BestellStroke	750 mm
Cushioning	Einstellbare Endlagendämpfung
Magnetic/Non-magnetic	Nicht magnetisch
Theoretical Force	6920 N
Materials - Barrel	Eloxierte Aluminiumlegierung
Material - Lager	Aluminium-Druckguss
Material - Elastomere	Nitrile rubber

Material - Kolbenstange	Rostfreier Stahl (martenitisch)
Material - Kolben	Aluminium-Druckguss
Series	RM/900
Series	Martonair
Marken	Norgren

VERSION

Dw P-Zyl..

MANUFACTURER

Genuine Norgren.