

Double-acting Profile Cylinder - Norgren KM/8025/MF/50

Item no. NRG-KM/8025/MF/50

Manufacturer Norgren

Double-acting Profile Cylinder. Norgren pneumatic cylinder converts compressed air into linear motion and force.

TECHNICAL DATA

Norm	ISO 6432
Weight	0.1 kg
Zolltarifnummer	84123100



DESCRIPTION

Norgren pneumatic cylinder converts compressed air into linear motion and force. Rugged design for precise, reliable working strokes in automation.

TECHNICAL DATA

BetriebsMedium	Druckluft
Ambient temperature	-10 ... 80 °C
Pressure range	1 ... 10 bar
Norm	ISO 6432
Port	G1/8
Zylinderdurchmesser	25 mm
BestellStroke	50 mm
Cushioning	Endlagenpuffer
Magnetic/Non-magnetic	Magnetisch
Theoretical Force	294 N
Materials - Barrel	X5 Cr Ni 18 10 (1.4301: AISI 304)
Material - Dämpfung	Polyurethan

A1-ESD equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com
fluidics-equipment.com

Page 1/2

Material - Kolbenstange	material x10 cr ni s 18 9 (1.4305- aisi 303)
Material - Kolben	POM
Material - Dichtungen	Nitril
Series	KM/8000/M
Marken	Norgren

VERSION

double-acting Profile Cylinder.

MANUFACTURER

Genuine Norgren.