

Double-acting Profile Cylinder - Norgren RM/9125/150

Item no. NRG-RM/9125/150

Manufacturer Norgren

Double-acting Profile Cylinder. Norgren pneumatic cylinder converts compressed air into linear motion and force.

TECHNICAL DATA

Weight	1 kg
Zolltarifnummer	84123100



DESCRIPTION

Norgren pneumatic cylinder converts compressed air into linear motion and force. Rugged design for precise, reliable working strokes in automation.

TECHNICAL DATA

BetriebsMedium	Druckluft
Ambient temperature	-20 ... 80 °C
Pressure range	2 ... 10 bar
Port	G1/8
Zylinderdurchmesser	1-1/4"
BestellStroke	150 mm
Cushioning	Einstellbare Endlagendämpfung
Magnetic/Non-magnetic	Nicht magnetisch
Theoretical Force	406 N
Materials - Barrel	Eloxierte Aluminiumlegierung
Material - Lager	Aluminium-Druckguss
Material - Elastomere	Nitrile rubber

Material - Kolbenstange	Rostfreier Stahl (martenitisch)
Material - Kolben	Aluminium-Druckguss
Series	RM/900
Series	Martonair
Marken	Norgren

VERSION

double-acting Profile Cylinder.

MANUFACTURER

Genuine Norgren.