

Aluminum Hollow Plunger Hydraulic Cylinder, 1489 kN, 150 mm Stroke - Enerpac RARH1506

Item no. ENP-RARH1506

Manufacturer Enerpac

Aluminum hollow plunger cylinder (RARH series) with 1489 kN of force and a 150 mm stroke. The hollow plunger build suits both push and pull tasks.

TECHNICAL DATA

Country of Manufacture	United States
Hinweis	Industriewerkzeuge
Kapazität (kN)	1000-2000 kN
Serie	RARH
Weight	56.2 kg



DESCRIPTION

The RARH1506 is a double-acting hollow plunger cylinder with 1489 kN of force and a 150 mm stroke, whose through-hole supports both push and pull tasks such as tensioning and drawing.

BENEFITS

- Hollow plunger design for both push and pull work such as tensioning or drawing components
- Double-acting for fast plunger retraction, built-in safety valve prevents accidental over-pressure
- Lighter and with a shorter collapsed height than comparable RACH models at 1489 kN
- Composite bearings and hardened coating raise side-load resistance and extend service life
- Floating centre tube increases seal life, handles and CR400 coupler fitted as standard

TECHNICAL DATA

- Capacity: 1489 kN
- Stroke: 150 mm
- Action: double-acting, hollow plunger
- Operating pressure: 700 bar
- Collapsed height: 364 mm
- Extended height: 514 mm
- Outside diameter: 280 mm
- Bore diameter: 190 mm

A1-ESD equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com
fluidics-equipment.com

- Weight: 56.2 kg
- Series: RARH
- Standard: ASME B30.1